

Machine Tube Luminaire



INPUT VOLTAGE	: 24V AC/DC, 110 AC, 230 V AC
WATTAGE	: 18 WATTS - SINGLE TUBE
CONTROL GEAR	: ELECTRONIC BALLAST FOR 24V AC/DC CU BALLAST FOR 230V/AC
LUMENS	: 1130 Lm, Cool Day Light
LUMINAIRE BODY	: BOROSILICATE GLASS
DIAMETER	: 60 MM
FASTENING	: END BRACKETS
PROTECTION GRADE	: IP 67
WEIGHT (W/O CONTROL GEAR)	: KGS. (Approx.)
REPLACEMENT TUBE	: 18W/11 -860
CABLE LENGTH	: 1.5 Mtr. for 24V AC/DC, 110V AC 3Mtrs for 230V AC

EXTERNAL BALLAST

MODELS	I/P VOLTAGE	LENGTH IN MM APPROX.
SMC - CNC - 3-1-E	24V AC/DC	335 MM
SMC - CNC - 3-2-E	110V AC	335 MM
SMC - CNC - 3-3-E	230 VAC	335 MM

INTERNAL BALLAST

MODELS	I/P VOLTAGE	LENGTH IN MM APPROX.
SMC - CNC - 3-1-I	24V AC/DC	465 MM
SMC - CNC - 3-2-I	110V AC	395 MM
SMC - CNC - 3-3-I	230 VAC	375 MM

SURYA MARKETING CORPORATION
AN ISO 9001 - 2000 CERTIFIED MANUFACTURER