

## Machine Tube Luminaire



INPUT VOLTAGE	: 24V AC/DC, 110 AC, 230 V AC
WATTAGE	: 18 WATTS, (9 WATTS X 2)
CONTROL GEAR	: ELECTRONIC BALLAST FOR 24V AC/DC, 110V AC CU BALLAST FOR 230V/AC
LUMENS	: 1150 Lm, Cool Day Light
LUMINAIRE BODY	: BOROSILICATE GLASS
DIAMETER	: 60 MM
FASTENING	: END BRACKETS
PROTECTION GRADE	: IP 67
WEIGHT (W/O CONTROL GEAR)	: 1.4 KGS. (Approx.)
REPLACEMENT TUBE	: 9W/865 -G23 - 2 Pin X 2
CABLE LENGTH	: 1.5 Mtr. for 24V AC/DC, 110V AC 3Mtrs for 230V AC

### EXTERNAL BALLAST

MODELS	I/P VOLTAGE	LENGTH IN MM APPROX.
SMC - CNC - 4-1-E	24V AC/DC	495 MM
SMC - CNC - 4-2-E	110V AC	495 MM
SMC - CNC - 4-3-E	230 VAC	495 MM

### INTERNAL BALLAST

MODELS	I/P VOLTAGE	LENGTH IN MM APPROX.
SMC - CNC - 4-1-I	24V AC/DC	665 MM
SMC - CNC - 4-2-I	110V AC	685 MM
SMC - CNC - 4-3-I	230V AC	605 MM

**SURYA MARKETING CORPORATION**  
AN ISO 9001 - 2000 CERTIFIED MANUFACTURER