

Machine Tube Luminaire



INPUT VOLTAGE	: 24V AC/DC, 110 AC, 230 V AC
WATTAGE	: 55 WATTS- SINGLE TUBE
CONTROL GEAR	: ELECTRONIC BALLAST FOR 24V / 110 AC/ 230 V AC
LUMENS	: 4500 Lm COOL DAY LIGHT
LUMINAIRE BODY	: BOROSILICATE GLASS
DIAMETER	: 60 MM
FASTENING	: END BRACKETS
PROTECTION GRADE	: IP 67
WEIGHT (W/O CONTROL GEAR)	: 2.5 KGS. (Approx.)
REPLACEMENT TUBE	: PLL-4P-55W/865 -2G11
CABLE LENGTH	: 1.5 Mtr. for 24V, 110V AC 3Mtrs for 230V AC

**EXTERNAL BALLAST**

MODELS	I/P VOLTAGE	LENGTH IN MM APPROX.
SMC - CNC - 7-1-E	24V AC/DC	595 MM
SMC - CNC - 7-2-E	110V AC	595 MM
SMC - CNC - 7-3-E	230 V AC	595 MM

**INTERNAL BALLAST**

MODELS	I/P VOLTAGE	LENGTH IN MM APPROX.
SMC - CNC - 7-1-I	24V AC/DC	730 MM
SMC - CNC - 7-2-I	110V AC	620 MM
SMC - CNC - 7-3-I	230V AC	825 MM